



## STANDARD PRILLED CALCIUM SULFATE

### Guaranteed Analysis

Calcium (Ca) .....23.28%  
 Sulfur (S) .....18.62%  
 Calcium Sulfate (CaSO<sub>4</sub>).....79.00%  
 California  
 Gypsum Equivalent .....100%

**Derived From:** Mined Hydrated Calcium Sulfate.

### Grind Analysis

100% passing 100 mesh  
 90% passing 140 mesh  
 53% passing 200 mesh  
 25% passing 325 mesh

### Characteristics of Prilled Calcium Sulfate

Moisture Content ..... <1%  
 Water Soluable Binder ..... 5%  
 Angle of Repose ..... 30°  
 SGN ..... 125  
 UI ..... 49  
 Bulk Density, Loose ..... 68 lbs./cu.ft.  
 Bulk Density, Tapped ..... 75 lbs./cu.ft.

- ◆ Cal-CM Plus Standard Prilled Calcium Sulfate is a registered material for use in Organic Agriculture by the Washington State Department of Agriculture. It is also listed by OMRI for use in organic production.
- ◆ Use in accordance with the recommendations of a qualified individual or institution, or according to an approved nutrient management plan.
- ◆ To locate a dealer near you, call the numbers listed below. For additional information visit our Website: <http://www.calcmplus.com>

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.htm>

**TOTE**  
**Net Weight: 2000 lbs.**



**MANUFACTURED BY:**  
 Art Wilson Co., P.O. Box 20160, Carson City, NV 89721  
 Ph. 775-882-0700 / Toll Free 888- 497-6463 / Fax 775-882-0790 / Email: [sales@calcmplus.com](mailto:sales@calcmplus.com)