



HP 50



GENERAL USE INFORMATION – READ ENTIRE LABEL BEFORE USING THIS PRODUCT

HP 50 HYDROGEN PEROXIDE

HP 50 is a Hydrogen Peroxide solution designed for use as an oxidizing irrigation system and line cleaner which assists in controlling sediment build up.

ACTIVE INGREDIENT:
HYDROGEN PEROXIDE

50%

INERT INGREDIENT:

50%

Total

100.0%

DANGER



HAZARD STATEMENTS: Causes severe skin burns and eye damage.
May intensify fire; oxidizer.
May be corrosive to metals.
Harmful if swallowed.
May be harmful in contact with skin.

PRIOR TO USE:

This product is not classified as a fertilizer or soil amendment.
Not for use as a potable water additive.
HP 50 is **NOT A DISINFECTANT**. Do not use as a disinfectant. Not for potable or drinking water use.

DIRECTIONS FOR USE:

AGRICULTURAL, GOLF COURSE and HORTICULTURAL USES:

Treatment of Irrigation Water Systems:
Apply through drip lines with water at 1.5 to 3ppm.
Apply to water wells at 3,000 to 120,000 ppm.

PRECAUTIONARY STATEMENTS:

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

IF ON SKIN (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/ shower.

IF SWALLOWED: Call a poison control center or doctor immediately. Do not induce vomiting unless told to do so by a poison control center or doctor.

Keep away from heat/sparks/open flames/hot surfaces - No smoking. Keep/ Store away from combustible materials. Take any precaution to avoid mixing with combustibles.
Keep only in original container.

PHYSICAL OR CHEMICAL HAZARDS STRONG

OXIDIZING AGENT CORROSIVE: Mix only with water below 140° F. Product must be diluted in accordance with label directions prior to use. This product is not combustible; however, at temperatures exceeding 156°F, decomposition occurs releasing oxygen. The oxygen released could initiate combustion.

PERSONAL PROTECTIVE EQUIPMENT:

Handlers who may be exposed to the undiluted product through mixing, loading, application, or other tasks must wear coveralls over long-sleeved shirt and long pants, rubber gloves, chemical resistant footwear plus socks, and protective eyewear (goggles or face shield). Follow manufacturer's instructions for cleaning/ maintaining PPE.

STORAGE AND DISPOSAL:

STORAGE: Never return this product to the original container after it has been removed. Avoid all contaminants, especially dirt, caustic, reducing agents, and metals. Contamination and impurities will reduce shelf life and can induce decomposition. Avoid damage to containers. Keep container closed at all times when not in use. Keep container out of direct sunlight. To maintain product quality, store at temperatures below 86°F. **PROCEDURE FOR LEAK OR SPILL:** Stop leak if this can be done without risk. Shut off ignition sources: no flames, smoking, flares, or spark producing tools. Flush spilled material with large quantities of water.

CONTAINER HANDLING:

(Containers equal to or less than 5 gallons): Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Then offer for recycling if available or puncture and dispose of properly.

Manufactured by:

CYC Solutions Company

3085 N Cessna Way
Casa Grande, AZ 85122

24 hr. Emergency ChemTrec No.: 800-424-9300

D.O.T.: UN2014, Hydrogen Peroxide, Aqueous Solution (50%); 8, 5.1, PGII

Package size: 250 Gallons (946.353L)
Density: 9.98 Lbs. per Gal at 68 degrees F